

# deais ecologico

ecological release-agent with vegetal base for universal use

Edition:1 December 2010

**Technical Department** 

## **Description:**

Ecological release-agent in liquid shape in vegetal base without solvents for concrete prefabs and construction in general.

# **TechnicalFeatures:**

Aspect: Oily liquid Colour/s: Amber Density: 0,93±Kg./Lt. ± 0,05 Odour: Characteristic

## **Coverage:**

30 to 40 sqm/ LT according with support and use.

## Uses:

On industries dedicated to the manufacturing on prefab concrete and construction in general. It can be applied to all types of metallic moulds, wood, plastic, polyester, elastomers, polyestirene, etc

# Features & benefits:

ECOLOGICAL EASY TO USE DOES NOT EMIT VAPOUR PROTECT MOULDS DOES NOT SPOT IT ALLOWS HIGH QUALITY SURFACES AVOIDS THE MORTAR AND



#### CONCRETE ADHERENCES TO THE MOULDS

#### **Surface preparation:**

The surface must be pretty cleaned, free of greases, withour rust, concrete wastes or dust of cement in order to avoid spots on concrete.

## **Application:**

-Apply without dilute.

-It must be applied by brush, roller or spray can on the mould having special care avoiding parts free of release-agent.

-The product avoids the adherence of the concrete with the moulds.

-It does spot neither concretes nor mortars.

#### **Clean up:**

With soap and water.

### **Storage:**

1 year in their original packages and tightly closed.

## **Packaging:** Available in packs of:

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of it's useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this



# deais ecologico

document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS ©TEAIS S.A. - All rigths reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña Telf.: 981 600 966 - Fax: 981 601 508 - Email: info@teais.es