

### Description:

IMPRIMAIS is a water based primer that acts as a penetrating sealer used for the treatment of new supports. It improves and makes the fixing of paint easier by also reducing the amount of paint to be used.

### Uses:

It is used to prepare newly rendered supports as well as backgrounds made of cement and plaster. The primer is appropriate for sealing and penetrating at the same time.

### Features & benefits:

PAINT APPLICATION AND EFFICIENCY ARE IMPROVED.

### Surface preparation:

The background of application must be clean, dry and free of grease.

### Application:

- Shake briskly before using the product.
- Apply with a paint brush or roller by diluting in a proportion of 1:5.

### Technical Features:

Density: 1.05 Kg/L ( $\pm$ ) 0.05 at 20°C  
Viscosity: 12.5  $\pm$  2.5 s at 20°C. Ford cup: 4 mm.  
Dry upon touching:

### Coverage:

25 m<sup>2</sup> per l.

### Clean up:

Clean using large amounts of water.

### Storage:

It is recommended to store this product for 2 years in tightly closed original packages in a cool dry place.

### Packaging:

Available in packs of:

- .: 1 L
- 5 L
- 25 L

### Health and safety advice :

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.