

TECHNICAL DATA

Stik

Adhesive tape

Technical specification

Adhesive jointing tape made of waterproof non-woven anti-stretching. Supplied in rolls 60 mm x 25 m.



PHYSICAL CHARACTERISTICS	Standard	Unit	Stik	Tolerance
Thickness	EN 1849-2	mm	0,65	± 15%
Length		m	25	
Width		mm	60	
Colour			gray/green	

TECHNICAL CHARACTERISTICS	Standard	Unit	Stik	Tolerance
Tensile strength	EN 13859-1	N/5cm	240	± 15%
elongation	EN 13859-1	%	35,0	± 5%
Laceration to the nail	EN 13859-1	N	160	± 15%
UV resistance		Months	4	
Adhesive force	AFERA 5001	N/25mm	35	± 3
Temperature resistance (tack permanence)		°C	-20 / +70	
Recommended application temperature		°C	+5 / +40	
Water vapour trasmission Sd	EN 13859-1	m	0,070	

INSTALLATION INSTRUCTIONS



Remove the protective film and seal the joints of the rolls, wall panels and Profile

The suggestions and technical information given above represent our knowledge regarding the properties and the product's uses. ISOLGOMMA reserve the right to modify or update this data without prior notice. This document is the property of ISOLGOMMA and all rights are therefore reserved.