

Description:

Penetrant sealer water-based that can be used as preparation of new supports. Makes easier the fixing and subsequent painting and at the same time reduces the quantity of paint to use. The paint looks more uniform by its action.

Uses:

As the preparation of primers in new covering, cement and gypsum. Seals and penetrates quite good.

Features & benefits:

IMPROVES THE PAINT APPLICATION IMPROVES THE COVERING OF THE PAINT* SEALANT* EVEN THE ABSORPTION*

Surface preparation:

The surface must be clean, free of greases and dry.

Clean up:

with plenty of clean water.

Application

- Shake strongly the product before applying.
- Apply with brush or roller diluted in proportion until 1:5 with water.
- If it is used in outdoor not apply with rain forecast, strong winds, freeze or any adverse weather condition.

Packaging:

Available in packs of:

- 1 Litre 20 Packages per box
- 5 Litre 4 Packages per box

Storage:

Store in a dry and cool place for 2 years maximum in their original packages and tightly closed.

Health and safety advice:

Consult the safety information on the label on each package, and for more information refer to the product Material Safety Data Sheet.

Technical features:

Density	1,05 Kg/L. (+-) 0,05 at 20°C
Dry for repainting	after 8 hours at 20°C y 65% RH
Dry upon touching	< 30 min. at 20°C, 65% R.H.
Temperature of work	from 5°C to 30°C
Viscosity	12,5 ± 2,5 seg. At 20°C. Layer Ford: 4 mm
zzz	

Coverage:

25 sqm per litre.

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña
Telf.: 981 602 111 - Fax: 981 601 508 - Email: comex@teais.es