

Description:

Lastois Roca is an elastic mortar sealant, with mineral and pigment charges. It has high resistance against atmospheric elements and UV radiation. The product when is cured becomes waterproofing, and once it is dry, allows painting on it with water-paints.

Uses:

Lastois Roca is used for sealing several materials of construction such as frames, aluminium windows, wood, iron, PVC, etc. It is used for filling and sealing cracks, joints, chimney finishes, fiber-cement, slate, etc. Plasteboards, prefabconcrete, stone pieces, marble, etc. It is suitable for sealing and finishing Exterior Thermal Insulation Systems because its plasticity and transpiration properties.

Preparación de la superficie:

The support of the application must be clean, dried and cured free of permanent moisture.

Modo de aplicación:

- It is applied by silicon gun, spatula, trowel, etc..
- The product has pasty consistence.



- HIGH ADHERENCE
- UV RESISTANT
- WEATHER RESISTANT
- HIGH AESTHETIC PROPERTIES
- PAINTABLE

Packaging: 0.3 dm³
Coverage: 12m in 5x5mm joint



Lastois roca

elastic mortar sealant



White



Red tile




Off white



Brown



Sand



Grey Porriño



Santiago Stone



Black



Pink Porriño



Translucent





lastois roca

Elastic mortar sealant.

Edition: 1

09/2014

Technical department

Description:

LASTOIS ROCA is an elastic mortar sealant, with mineral and pigment charges. It has high resistance against atmospheric elements and UV radiation. The product when it is cured becomes waterproofing, and once it is dry, allows painting on it with water-paints.

Uses:

LASTOIS ROCA is used for sealing several materials of construction such as frames, aluminium windows, wood, iron, PVC, etc.
It is used for filling and sealing cracks, joints, chimney finishes, fiber-cement, slate, etc. Plasterboards, prefabricated concrete, stone pieces, marble, etc. It is suitable for sealing and finishing Exterior Thermal Insulation Systems because of its plasticity and transpiration properties.

Features & benefits:

HIGH ADHERENCE UV RESISTANT* WEATHER RESISTANT* HIGH AESTHETIC PROPERTIES* PAINTABLE*

Surface preparation:

The support of the application must be clean, dried and cured free of permanent moisture.

Clean up:

The tools must be cleaned with plenty of water while the material is wet.

Application

- It is applied by silicon gun, spatula, trowel, etc..
- The product has pasty consistency.

Packaging:

Available in packs of:

0,31 Cubi 12 Packages per box

Storage:

1 year in their original packages stored in a cool and dry place protected from the weather.

Health and safety advice:

Consult the safety information on the label on each package, and for more information refer to the product Material Safety Data Sheet.

Technical features:

Aspect	Thixotropic paste
Colour/s	white, grey, black, brown, tile-red, sand, santiago.
Density	1,65
PH	8
Totally dry	5mm each 12 hours to 20°C

Coverage:

1,65 kg/l

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is not possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS
©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Artoixo, A Coruña
Telf.: 981 602 111 - Fax: 981 601 508 - Email: comex@teais.es

