

powder product used for outdoor plastering

Edition:6 October 2010

Technical Department

Description:

Powder product based in cement to be mixed with water so as to form a plastic paste used for plastering, whitewash cracks and chippings on walls and ceilings, both in interiors and exteriors.

TechnicalFeatures:

Water absorption: $35 \pm 3\%$

Powder density: $0,85 \text{ g/cc.} \pm 0,05$

Mass of density: $1,900 \text{ g/cc.} \pm 0,05$

Open time: $> 45 \text{ min.}$

Water retention: $> 97\%$

Capillarity: Adherence: $> 5 \text{ kg/cm}^2$

Compressive resistance: $> 150 \text{ kg/cm}^2$

Flexural strength resistance: $> 45 \text{ kg/cm}^2$

Colour/s: white

ZZZ: ZZZ

ZZZ: ZZZ

ZZZ: ZZZ

Coverage:

1 sqm per kg in layer of 1 mm.

Uses:

Used so as to eliminate irregularities on surfaces to be painted afterwards (in interiors and exteriors), to level rendered supports as well as to eliminate cracks and fissures.

Features & benefits:

EASY APPLICATION EXCELLENT WORKABILITY STRONG HARDNESS

Surface preparation:

The background of application must be clean and perfectly dry, free of grease, saltpeter and dust, being compact and firm.

Application:

- To be mix with water.
- Apply it by trowel or spatula on thin layer.
- Once EMPLAIS EXTERIORES is dry apply TEAIS Paint on it as decorative coating.
- Before painting on the plaster let it dry at least 50 hours since the last coat.

Clean up:

Clean with large amounts of water.

Storage:

It is recommended to store this product for 2 years in its tightly closed original packages protected against bleakness.

Packaging:

Available in packs of:

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is not possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS ©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña Telf.: 981 600 966 - Fax: 981 601 508 - Email: info@teais.es