

### Description:

EPOAIS D consists of a two component epoxy paint based on epoxy resins and innocuous pigments. It is in compliance with UNE-53550 standard on global residual migration in the environment

### Uses:

It is suitable for slaughterhouses, butcher shops, fishmongers, milk industry, food industry, food industry in general, etc.

### Features & benefits:

APPROPRIATE FOR THE FOOD INDUSTRY. EXCELLENT CHEMICAL AND MECHANICAL RESISTANCE.

### Surface preparation:

The background of application must be clean, free of grease, dust, cracks and chippings, by being compact and dry.

### Application:

- Once mixed, the open time of the mix is 6 hours (after this time, it remains liquid but its use is not recommended). Mix both components in the following proportions (check for white and other colours):

in weight: 78.78A/21.22B

in volume: 85A/15B

- Apply with a paint brush or roller.

- EPOFOS primer is used on metallic supports and IMPRIDUR primer on cement based supports.

### Technical Features:

Density: component "A": 1.45 Kg/Litre at 20°C/65% component "B": 0.95 Kg/Litre at 20°C/65%

Dry upon touching: 20 minutes at 20°C/65%

Totally dry: 8 Hours at 20°C/65%

Dry for repainting: 18-36 Hours at 20°C/65%

Combustion point: > 15°C TAG closed cup.

Colour/s: blanco and other colours upon request.

### Coverage:

7 m<sup>2</sup> per kg in 50 micron coating.

### Clean up:

Clean using our solvent DISOLVENTE EPOXI.

### Storage:

It is recommended to store this product for 2 years in tightly closed original packages.

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



paints  
epoais d  
food industry paints

### Packaging:

Available in packs of:

:: 4.7 Kg

24 Kg

### Health and safety advice :

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña

Telf.: 981 600 966 - Fax: 981 601 508 - Email: info@teais.es