

MEGAMAT 500


VIBRATION CONTROL



VIBRATION INSULATION PANEL MADE OF END-OF-LIFE TYRES RUBBER GRANULES AND FIBRES

■ TECHNICAL SPECIFICATION

Anti-vibration material supplied in panels, thickness 12,5/25/50 mm, made of rubber granules and fibres from End-of-Life Tyres (ELTs) compacted using a polyurethane binder in a hot process. A non-woven, non-stretch synthetic membrane is applied on one side of panel, for added protection; density 500 kg/m³. Panels dimensions are m 1,20 length, m 0,80 width. To be used for static and dynamic loads up to 0.25 N/mm².



■ APPLICATION AREA

Application fields	Load	Deformation
Static	up to 0,05 N/mm ²	~ 10%
Static and Dynamic	up to 0,25 N/mm ²	~ 30%
Load peaks (short time)	up to 0,80 N/mm ²	~ 50%

■ TECHNICAL DATA

		Tolerance	Standard
Thickness	12,5 - 25 - 50 mm	± 2	
Length	1,20 m	± 2%	
Width	0,80 m	± 2%	
Density	500 kg/m ³	± 10%	
Stress at strain 10%	0,05 N/mm ²	± 10%	EN ISO 29470
Static Modulus of Elasticity (Es) - strain 10%	0,55 N/mm ²	± 10%	EN ISO 29470
Dynamic Modulus of Elasticity (Ed) - strain 10%	1,80 N/mm ²	± 10%	
Loss factor (η)	0,143	± 10%	
Thermal conductivity coefficient (λ)	0,090		EN 12668
Inflammability	E		EN 13501-2

MEGAMAT 500

VIBRATION CONTROL




INSTALLATION INSTRUCTIONS FOR MEGAMAT

- 1 Prepare the excavation for the foundations and make the sub-foundation pit



- 2 Glue the MEGAMAT panels along the pit walls, taking care to fit them together without leaving gaps or cavities along the joins



- 3 Seal the joins between the panels carefully with Stik tape




- 4 Lay the MEGAMAT panels on the bottom of the pit, taking care to fit them together without leaving gaps or cavities along the joins



- 5 Seal the joins between the panels carefully with Stik tape



- 6 Lay a waterproof protective sheet over the MEGAMAT



- 7 Prepare and position the reinforcing bars and cast the reinforced concrete foundation plinth



- 8 Conclude with the installation of the machinery



SEE THE REFERENCES > VISIT THE WEBSITE



www.isolgomma.com
PRG-MOD. 15 - REV. 4.1 14/07/25 EN

© Isolgomma Srl. The data and images are indicative and can be changed at any time without notice

CONTACT THE TECHNICAL DEPARTMENT FOR MORE INFORMATION


ISOLGOMMA
SILENCE MAKERS

MEGAMAT 500


VIBRATION CONTROL




LOAD DEFLECTION CURVE



STATIC MODULUS OF ELASTICITY



DYNAMIC MODULUS OF ELASTICITY




MEGAMAT 500

VIBRATION CONTROL



NATURAL FREQUENCY



VIBRATION ISOLATION EFFICIENCY

