

Description:

LASTOIS CUBIERTAS consists of an elastomer resin based waterproofing liquid containing additives and high resistance additives and pigments. It must always be protected and reinforced so that it can work perfectly.

Uses:

It is used for waterproofing passable non-passable decks. For waterproofing terraces, roofs, decks, balconies, pipes, etc.

Features & benefits:

EXCELLENT ELASTICITY.HIGH ADHERENCE.EASY APPLICATION.

Surface preparation:

The background of application must be clean, free of grease, oil and dust.

Application:

- Apply one coating of IMPRILURRIS on the support using a paint brush or roller.
- Once priming is dry, apply one coating of LASTOIS CUBIERTAS followed by embedding with FIBRAIS 300 reinforcing mesh.
- Then apply a second coating of LASTOIS CUBIERTAS. It is very important to take into account the efficiency that is indicated (2kg/m2).
- Apply one coating of protection based on PAVIGRAIS or LASTOIS FH-CV as required.

TechnicalFeatures:

Density: 1.3 kg/dm3 ± 0.05 kg/m3

Viscosity: 20.000 mPa·s ± 10.000 mPa·s

-: Great adherence to the support and easy application.

Colour/s: Rojo teja, blanco, negro and Gris.

Coverage:

2 kg per m2.

Clean up:

Clean using large amounts of water.

Storage:

It is recommended to store this product for 2 years in tightly closed original packages in a cool dry place, with temperatures above 5°C and below 38°C.

Packaging:

Available in packs of:

.: 1 Kg

5 Kg

20 Kg

Health and safety advice :

R43 -- May cause sensitisation by skin contact



The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.