

## **NSF Product and Service Listings**

These NSF Official Listings are current as of Monday, October 19, 2015 at 12:15 a.m. Eastern Time. Please contact NSF International to confirm the status of any Listing, report errors, or make suggestions.

Alert: NSF is concerned about fraudulent downloading and manipulation of website text. Always confirm this information by clicking on the below link for the most accurate information: http://info.nsf.org/Certified/PwsComponents/Listings.asp?

Company=0C660@Standard=061@

## NSF/ANSI 61 Drinking Water System Components - Health Effects

NOTE: Unless otherwise indicated for Materials, Certification is only for the Water Contact Material shown in the Listing. Click here for a list of Abbreviations used in these Listings. Click here for the definitions of Water Contact Temperatures denoted in these Listings.

## Kryton International Inc.

1645 East Kent Avenue Vancouver, BC V5P 2S8

Facility: Vancouver, British Columbia, Canada

## Protective (Barrier) Materials

Trade Designation	Water Contact Size Restriction	Water Contact Temp	Water Contact Material
Concrete Admixtures			
KIM-AE	[1]	C. HOT	CMNT
KIM-ES	[1]	C. HOT	CMNT
KIM-HS	[1]	C. HOT	CMNT
Krystol Internal Membrane	[1]	C. HOT	CMNT
Krystol Repair Grout	[1]	C. HOT	CMNT
Krystol T1	[1]	C. HOT	CMNT
Krystol T2	[1]	C. HOT	CMNT
Krystol Waterstop Grout	[1]	C. HOT	CMNT
Krystol Waterstop Treatment	[1]	C. HOT	CMNT

<sup>[1]</sup> Certified for use in tanks 6000 gallons and greater. Maximum use level of admixture is 2% of cement by mass.