

# Technical Commercial Data Sheet

## Bitufond

### **Bulged membrane in high-density polyethylene(HDPE).**



#### Dimensional features

Length	20 m $\pm$ 1%
Width BITUFOND 1,5 x 20	1,5 m $\pm$ 1%
Width BITUFOND 2,0 x 20	2 m $\pm$ 1%
Width BITUFOND 2,5 x 20	2,5 m $\pm$ 1%

#### Description

Bulged membrane in high-density polyethylene (HDPE).

#### Application

- Use Personal Protective Equipment as requested by law;

#### Vertical applications on foundations and earth retention walls:

Thanks to its special selvedge free from bulges, the vertical application can be carried out by a simple fixing procedure:

- Overlap layers of at least 20 cm;
- Fix the membrane with steel nails, with at least 1 nail per meter and increasing the nails number according to the foundation depth;
- Proceed with the filling of earth.

#### Horizontal applications:

As an alternative to the traditional lean concrete layer, the slabs can be realised by employing BITUFOND with clear time and material costs saving:

- Level the ground
- Cover the ground with some centimeters of sand,
- Apply BITUFOND membrane with the bulges facing downwards
- Overlap layers for at least 20 cm; with the interposition of a double adhesive tape;
- Proceed with the reinforcement application and with the casting of the screed, which will be more stable thanks to the action of the spreading of loads performed by the BITUFOND membrane.

#### Recommended use


Waterproofing of foundations, basements, earth retention walls, green roofs, moist walls, flat roofs etc.

#### Storage

Keep the rolls in warehouse, not exposed to the sun rays and at a temperature not below +5°C. Keep the rolls in the upright position. It is advisable to use the product within 2/3 months from delivery.

Type	N° rolls per pallet	m <sup>2</sup> per pallet
BITUFOND 1,5 X 20	12	360
BITUFOND 2 X 20	12	480
BITUFOND 2,5 X 20	12	600

CODE: STCBE 022  
REVISION: 01a  
DATE: DECEMBER 2013  
PAGE: 1/2



Isover Saint-Gobain  
è socio ordinario  
del GBC Italia

**Saint-Gobain PPC Italia S.p.A. – Attività Isover**  
Headquarters: Via Ettore Romagnoli, 6 – 20146 Milano  
Customer Service Bituver: Via G.Pastore, 15 - 66013 Chieti Scalo (CH) - Tel. 0871/599022 - Fax 0871/ 552483  
[www.bituver.it](http://www.bituver.it)



# Technical Commercial Data Sheet

## Bitufond


<i>Technical features</i>	<i>Unit.</i>	<b>BITUFOND</b>
<b>Compressive strength</b>	KN/m2	> 230
<b>Air volume between bulges</b>	l/m2	5,3
<b>Thermal stability</b>	°C	-40 / +80
<b>Disposition of openings</b>		Diagonally at 45°
<b>Bulges per m<sup>2</sup> selvedge excluded</b>	Nr.	1860
<b>Selvedge width</b>	mm	70 (± 10)
<b>Combustion class (DIN 4102)</b>		B2

Saint-Gobain Isover Italia S.p.A. quality system is certified according to EN ISO 9001.

The items of this technical data sheet are marketed by Saint Gobain PPC Italia. Consequently, the data here indicated have been obtained from the supplier's documents. The products are meant for proper modalities of application and storage and the technical data present in this document are indicative.

Saint Gobain PPC Italia has the right to carry out the changes or variations believed to be proper any time with no need of notice.

CODE: STCBE 022  
 REVISION: 01  
 DATE: DECEMBER 2012  
 PAGE: 2/2



Isover Saint-Gobain  
 è socio ordinario  
 del GBC Italia

**Saint-Gobain PPC Italia S.p.A. – Attività Isover**  
 Headquarters: Via Ettore Romagnoli, 6 – 20146 Milano  
 Customer Service Bituver: Via G.Pastore, 15 - 66013 Chieti Scalo (CH) - Tel. 0871/599022 - Fax 0871/ 552483  
[www.bituver.it](http://www.bituver.it)

