

Description:

MORIM is a dry pre-dosed mortar used for masonry jobs. It contains special additives that confer excellent mechanical resistance, waterproofing properties and workability.

Uses:

It is used in traditional renders, for setting up brick walls, concrete block walls, in basements, etc.

Features & benefits:

* EXCELLENT WORKABILITY * PREDOSED *
WATERPROOFING PROPERTIES *

Surface preparation:

The background of application must be clean, free of dust, loose particles, grease and oil. It is recommended to previously dampen the support in summer under high temperatures.

Technical features:

Adherence	> 10 kg/cm ²
Colour/s	White and grey
Compressive resistance	Aprox. 150 kg/cm ²
Curing density	1,80 +/- 0,05 gr/ml
Flexural strength resistance	> 35 kg/cm ²
Mass of density	2,05 +/- 0,05 gr/ml
Powder density	1,40 +/- 0,05 gr/ml
Temperature of work	5 to 30°C
Water absorption	18 + - 2%

Clean up:

Clean using large amounts of water.

Coverage:

2 kg/sqm per each mm of thickness

Application

- Mix MORIM with water (approximately 200 cc for every kg of MORIM).
- Mix manually or by using a low speed mixer(300 to 400 r.p.m.).
- Before the application, leave to stand for 2 to 5 minutes.
- Apply it using a trowel in a conventional manner getting a floated finish.

Packaging:

Available in packs of:

Grey	25 Kilos
White	25 Kilos

Storage:

It is recommended to store this product for 2 years in its tightly closed original packages protected against bleakness.

Health and safety advice:

Consult the safety information on the label on each package, and for more information refer to the product Material Safety Data Sheet.

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña
Telf.: 981 602 111 - Fax: 981 601 508 - Email: comex@teais.es